

## Product information

### Mini Breakout Cable I-V(ZN=B)H, OM3, Eca, 12-fibers

R308318  
101682120  
2000 m



The mini breakout cable is the ideal fiber to the desk solution for direct connector fitting. Due to its compact design it is easy to install, where space is limited it is perfect and economic solution. The 900µm tight buffers are individually colored and surrounded by glass yarns.

- Sheath: LSZH, green
- Fiber: multimode (MM) G50/125

030.1401 / similar product

#### Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO/IEC 11801:2002 IEC 60794-1-2 E1 IEC 60794-1-2 E11 IEC 60794-1-2 E3 IEC 60794-1-2 F1 IEC 60332-1 IEC 61034 IEC 60754-2
Protection class IP	IP 20
Cable type	mini breakout
Jacket material	LSZH
Fire rating	Eca
Cable jacket characteristics	Cable, metal-free Zero-halogen
Cable protection	No protection
Cable overall diameter	6.5 mm
Cable design	I-V(ZN)BH
Fiber type	multimode (MM)
Fiber class	OM3
Number of fibers	12
Conductor type	tight buffer
Fiber diameter	G50 / 125 µm

#### Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	2000 m
Color	green