


## Product information

### Central Loose Tube Cable A-DQ(ZN)B2Y, G.652.D, Eca, 12-fibers

R304156  
2000 m



The outdoor cable for cable and supply ducts. The design is a central gel-filled loose tube of a diameter of 2.8 mm for 2 - 16 fibers and 3.5 mm for 18 - 24 fibers. Specially processed and reinforced glass yarns provide the cable's rodent protection.

- Sheath: LLDPE, black
- Fiber: singlemode (SM) E9/125

090.2428 / similar product

### Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	IEC 60794-1-2 E11 IEC 60794-1-2 E3 IEC 60794-1-2 F1 IEC 60332-1 IEC 60332-3C IEC 61034 IEC 60754-2 ISO/IEC 11801:2002 ITU-T G.652.D IEC 60793-2-50:2004, B 1.3 IEC 60794-1-2 E1
Cable type	loose tube
Jacket material	LLDPE
Fire rating	Fca
Cable jacket characteristics	Cable, water-tight Cable, metal-free
Cable protection	Rodent protection
Cable overall diameter	6.5 mm
Cable design	A-DQ(ZN)B2Y
Fiber type	singlemode (SM)
Fiber class	G.652.D (OS1, OS2)
Number of fibers	12
Conductor type	loose tube, gel-filled
Fiber diameter	E9 / 125 µm

### Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	2000 m

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Color	black